



Joinpack



STRAPPING MACHINE



WE PACK PROMISES www.joinpack.com

Low Table Automatic Strapping Machine

Model No: A-93L

Low table strapping machine to serve heavy, bulky packages



Feature

- Digital regulator in PCB
- LED in PCB shows I/O status
- Proximity cam switch
- Instant heating system
- Weld cooling time adjustable
- 8 digit counter

Option

- Auto loading system
- Looping ejector
- Power roller driven table top (A93LAR)

Mobile Pallet Strapping Machine

Model No: S-72YO Patent No:201795

PP/PET pallet strapping machine with mobile track



Feature

- Mobile track for pallet strapping
- Low sealing head (550mm)
- Auxiliary feeding device
- Digital regulator in PCB
- LED in PCB shows I/O status
- PP/PET switch: to change the setting by one switch
- Proximity cam switch
- Weld cooling time adjustable

Option

- Ø406 Dispenser

Specification-Automatic Strapping Machine

Specification	Model No:	A-85AR	A-86	A-88AB	A-93AB	A-93AR
Speed		35 straps/min	50 straps/min	60 straps/min	30 straps/min	30 straps/min
Tension range	8~70 kgs for 9/12/15mm 3~30kgs for 5/6mm	○	○	○	15~70kgs	15~70kgs
Strap width	5,6,9,12,15mm (specified)	○	○	○	9,12,15.5 mm	9,12,15.5 mm
Sealing method	Heating element	○	○	○	○	○
Reel inside diameter	200, 230, 280 mm (specified)	○	○	○	○	○
Power supply	110 / 220 / 230 / 240V, 50 / 60Hz, 1PH 220 / 230 / 380 / 415 / 440V, 50 / 60Hz, 3PH	○	○	○	○	○
Conveyor speed		18m/min (50Hz) 21m/min (60Hz)		18m/min (50Hz) 21m/min (60Hz)	18m/min(50Hz) 21m/min(60Hz)	18m/min(50Hz) 21m/min(60Hz)
Table height	mm	805	805	805	805	815
Power consumption	KW	0.9kw	0.8kw	1.1kw	1.1kw	1.1kw
Standard arch size (W x H)mm		850W x 500H	650W x 500H	850W x 500H	850W x 600H	850W x 600H
Layout dimension (L x W x H)mm		1570 x 580 x 1430	1230 x 580 x 1430	1570 x 580 x 1430	1445 x 630 x 1525	1580 x 710 x 1538
Machine net weight	Kgs	227	195	253	260	286

Specification	Model No:	A-93N	A-93Y	A-93YMT	A-93L	S-72YO
Speed	30 straps/min	○	○	○	○	-
Tension range	15~70 kgs	○	○	○	○	○
Strap width	9, 12, 15.5 mm (specified)	○	○	○	○	○
Sealing method	Heating element	○	○	○	○	○
Reel inside diameter	200, 230, 280 mm (specified)	○	○	○	○	○
Power supply	110 / 220 / 230 / 240V, 50 / 60Hz, 1PH 220 / 230 / 380 / 415 / 440V, 50 / 60Hz, 3PH	○	○	○	○	○
Sealing height	mm	-	740	940	-	550
Table height	mm	800	-	850	440	-
Power consumption	KW	0.95 kw	0.95 kw	0.95 kw	0.95 kw	0.95 kw
Standard arch size (W x H)mm		850W x 600H	600W x 850H	600W x 650H	850W x 600H	-
Layout dimension (L x W x H)mm		1140 x 600 x 1520	1425 x 640 x 1715	1425 x 640 x 1943	1925 x 705 x 1480	1005 x 765 x 1120
Machine net weight	Kgs	228	228	280	280	210

*Specification subject to change without notice.