

Darwin: the mast.

TECHNICS

TECHNICAL DATA

Height	1381 mm
Width	1500 mm
Length	2805 mm
Turntable height	72 mm
Weight	450 kg
Power supply	230 VAC
Power absorption	0,75/1Kw



THE FIRST STEP TOWARD PACKAGING EVOLUTION.

Try to imagine a screw, ready to transform itself in a car to lead you anywhere you want: this is EvoPac Darwin. EvoPac Darwin it's our premium entry level machine. It features a unique telescopic-mast solution, an high-tech juice that raises up together with the carriage in order to save a lot of space (just 1381 mm height when turned off), to wrap smoother as ever and to give more value for your time! Once ordered, the machine reaches your wrapping area already fully assembled and ready to work: just plug and wrap! Fitted with high quality components, EvoPac Darwin can be tailored as you want to meet your requirements. That's the way to wrap.

evopac.com

The way to wrap



Darwin: the mast.

MAIN SPECIFICATIONS

Maximum height of the pallet: 2400 mm;
Loading plate: 1500 mm;
Maximum loading weight: 1200 kg;
Frequency controller for carriage speed management;
Frequency controller for turntable speed management;
Electromagnetic brake for film stretching;
Photocell for pallet height detection;
Safety stop at the base of the carriage;
Stop at 0 position;
6 working cycles;
Storage of 32 end user programs;
Wrapped pallet counter;
Autodiagnostic;
3 working modes: semi-manual;
semi-automatic;
fixed height;
2 years warranty.



EM-BRAKE



RACK AND PINION SYSTEM



DESIGNED FOR EASY ACCESS

MAIN OPTIONS

Power pre-stretch carriage;
Power pre-stretch with auto cut off system;
Adjustable power pre-stretch carriage;
Roping system;
Photocell for dark loads;
Top press;
Safety fences;
3000 mm max wrapping height;
2000 kg max pallet weight;
Weighing System;
Loading plate up to \varnothing 3000 mm;
Receiver for infrared/radio remote control.

EvoPac
The Way to Wrap



EVOPAC S.R.L.
Via Calcinaro, 2071 - 47521 Cesena (FC) - Italy
T. +39 (0)547. 630152

info@evopac.com
www.evopac.com